

EnduroSC PAS24 Access Controlled Communal

Not to scale







PUSH SIDE

PULL SIDE

Specification

This door is manufactured with a solid core and has hardwood lipping's to all 4 sides.

- · PAS24 tested from both directions
- Access control compatibility with various systems
- High density chipboard core
- 8mm hardwood lipping's on all 4 sides
- Overall thickness 54mm for NFR, FD30 and FD60
- Up to 35dB acoustic rated (with the correct seal arrangement)
- Tested to DD171 and classed as severe duty
- Choice of vision panel design options available

Ironmongery details

- High-security nightlatch
- High-security cylinder & turn override option
- High-security electric strike changeable on-site between fail safe/fail secure
- Lever handle or pull handle options
- Kick plate & fire signage

Door leaf/set Finishes

- Primed
- Veneered
- Laminated
- Factory-painted

Performance

- Fire tested to BS 476 part 22
- All fire rated doorsets manufactured under the stringent IFC Certification scheme
- Doorsets meet requirements of Approved Document M for clear opening widths

Suitable for...

- PAS24 Access Control Bin store, Refuse Room
- PAS24 Access Control Communal/ Circulation/ Stair etc.

FSC Certified

Sustainably sourced & carefully produced to design specification

Packaging

Protective packaging and delivered fully assembled in palletised form (varies per order)







